

	Standard	Result
Size	EN ISO 24342	Various
Thickness	EN ISO 24346	2,5 mm
Wear layer	EN ISO 24340	0,55 mm
Surface treatment		K-Guard+ PU coating
Guarantee <sup>1</sup>	Light industrial	15 years
	Commercial	15 years
	Residential	30 years
Slip resistance <sup>3</sup>	EN 13893	D5
	DIN 51130	R10
Recycling		Suitable
Phthalate free		Yes

<sup>1</sup> Subject to terms.

<sup>3</sup> Slip resistance is measured on freestanding ex-factory product. Slip resistance can be affected by many factors including but not limited to: product installation and underlayment, surface contamination, use, wear and how the product is maintained. Textural variation along the surface of the product can affect nominal values.

	Product Code
Solid Colours	V11
	V12
	V13
	V14
	V15
	V16
	V17
	V18
	V19
	V20
Stone Designs	SP111
	SP115

See our Opus and Solid colour technical data sheet for comprehensive technical information

**For more information:**

Designflooring = T: +44 (0) 1386 820 105 | F: +44 (0) 1386 820 132

Designflooring France = T: 01 57 32 39 13 | F: 01 57 32 39 14

Designflooring GmbH = T: 0211 469 59203 | F: 0211 469 59204

Designflooring Nederland = T: 020 200 8282 | F: 020 200 8386

Email: [info@designflooring.com](mailto:info@designflooring.com)

[www.designflooring.com](http://www.designflooring.com)

