



# Technical Data Sheet



	Standard	Result
Size	EN ISO 24342	See separate table
Thickness	EN ISO 24346	2,5 mm
Wear layer	EN ISO 24340	0,55 mm
Surface treatment		K-Guard+ PU coating
Guarantee <sup>1</sup>	Light industrial Commercial Residential	15 years 15 years 30 years
Bevelled edge		Micro
Mass per unit area	EN ISO 23997	4398 g/m <sup>2</sup>
Standards	EN 649/EN ISO 10582	Heterogeneous PVC
Classification	EN 685/EN ISO 10874 - Light industrial EN 685/EN ISO 10874 - Commercial EN 685/EN ISO 10874 - Domestic	42: Light industrial general 33: Commercial heavy 23: Domestic heavy
Reaction to fire	EN 13501-1	B <sub>fl</sub> -s1
Staining resistance	EN ISO 26987/EN 423	Excellent
Light fastness	EN ISO 105-B02	Pass (≥ 6)
Abrasion resistance	EN 660-2 EN ISO 10582	Group T Type 1
Flexibility	EN ISO 24344	Pass
Dimensional stability	EN 434/EN ISO 23999	Pass (≤ 0,25%)
Acoustic impact noise reduction	EN ISO 717-2/EN ISO 140-8	ΔL <sub>w</sub> = 2 dB
Electrical behaviour body voltage	EN 1815	Pass
Indentation - residual	EN 433/EN ISO 24343-1	Pass (≤ 0,1 mm)
Castor chair continuous use	EN 425/ISO 4918	Pass
Thermal resistance	ISO 8302	0,0097 m <sup>2</sup> /K/W Suitable for underfloor heating. Max 27°C
Slip resistance <sup>2</sup>	EN 13893 DIN 51130	DS R10
Adhesive		Please refer to our recommended adhesive list
Environmental	French VOC regulation (ISO 16000) Indoor Air Comfort  Floorscore SCS-EC10.3-2014 v4.0  Environmental Product Declaration DIBt/AgBB ISO 14001 / ISO 9001	A+  Gold certification; Compliant low emitting VOC emissions.  Indoor air quality certified; Compliant low emitting VOC emissions.  External third-party verified Type III EPD Pass Manufactured to quality and environment management systems standards
Recycling		Suitable
Phthalate free		Yes

<sup>1</sup> Subject to terms see website.

<sup>2</sup> Slip resistance is measured on freestanding ex-factory product. Slip resistance can be affected by many factors including but not limited to: product installation and underlayment, surface contamination, use, wear and how the product is maintained. Textural variation along the surface of the product can affect nominal values.

**For more information:**

Designflooring = T: +44 (0) 1386 820 105 | F: +44 (0) 1386 820 132

Designflooring France = T: 01 57 32 39 13 | F: 01 57 32 39 14

Designflooring GmbH = T: 0211 469 59203 | F: 0211 469 59204

Designflooring Nederland = T: 020 200 8282 | F: 020 200 8386

Email: [info@designflooring.com](mailto:info@designflooring.com)

[www.designflooring.com](http://www.designflooring.com)



20

EN 14041: 2004 (DOP 2017/OP/EN/02)
Notified body 0493
Floor coverings (internal)
ISO 10874 Class 23/33/42
Manufactured to ISO 10582



	Product Code	Size		Box Quantity		Slip Resistance DIN 51130
		mm	inches	m <sup>2</sup>	Pieces	
Wood Designs	WP411	1219,2 x 228,6	48,0" x 9,0"	3,345	12 Planks	R10
	WP414	1219,2 x 228,6	48,0" x 9,0"	3,345	12 Planks	R10
	WP418	1219,2 x 228,6	48,0" x 9,0"	3,345	12 Planks	R10
Stone Designs	SP213	457,2 x 609,6	18,0" x 24,0"	3,345	12 Tiles	R10
	SP119	457,2 x 457,2	18,0" x 18,0"	3,345	16 Tiles	R10
	SP120	457,2 x 457,2	18,0" x 18,0"	3,345	16 Tiles	R10
	SP121	457,2 x 457,2	18,0" x 18,0"	3,345	16 Tiles	R10
	SP122	457,2 x 457,2	18,0" x 18,0"	3,345	16 Tiles	R10
	SP719	152,4 x 914,4	6,0" x 36,0"	3,345	24 Planks	R10
	SP720	152,4 x 914,4	6,0" x 36,0"	3,345	24 Planks	R10
	SP721	152,4 x 914,4	6,0" x 36,0"	3,345	24 Planks	R10
	SP722	152,4 x 914,4	6,0" x 36,0"	3,345	24 Planks	R10
	SP723	457,2 x 914,4	18,0" x 36,0"	3,345	8 Tiles	R10
	SP724	152,4 x 914,4	6,0" x 36,0"	3,345	24 Planks	R10
	SP725	457,2 x 914,4	18,0" x 36,0"	3,345	8 Tiles	R10
	SP726	152,4 x 914,4	6,0" x 36,0"	3,345	24 Planks	R10
	SP727	152,4 x 914,4	6,0" x 36,0"	3,345	24 Planks	R10
	SP728	457,2 x 914,4	18,0" x 36,0"	3,345	8 Tiles	R10
	SP729	457,2 x 914,4	18,0" x 36,0"	3,345	8 Tiles	R10
	SP730	457,2 x 914,4	18,0" x 36,0"	3,345	8 Tiles	R10
	SP731	457,2 x 914,4	18,0" x 36,0"	3,345	8 Tiles	R10
	SP732	457,2 x 914,4	18,0" x 36,0"	3,345	8 Tiles	R10
	SP734	457,2 x 914,4	18,0" x 36,0"	3,345	8 Tiles	R10
	SP735	457,2 x 914,4	18,0" x 36,0"	3,345	8 Tiles	R10
SP736	457,2 x 914,4	18,0" x 36,0"	3,345	8 Tiles	R10	
SP737	457,2 x 914,4	18,0" x 36,0"	3,345	8 Tiles	R10	
SP738	457,2 x 914,4	18,0" x 36,0"	3,345	8 Tiles	R10	
SP739	457,2 x 914,4	18,0" x 36,0"	3,345	8 Tiles	R10	